

EXHIBIT A-1.2

COPIER / MFD SPECIFICATIONS, MODELS TO BE INSTALLED

The CONTRACTOR shall install Copier/MFDs and related accessories and software with the following specified working functionality and guaranteed minimum volumes for each Segment as listed and described below.

A. COPIER/MFD GENERAL SPECIFICATIONS

Segment	1	2	3	4	5	6
Device Model Numbers	Canon C3926	Canon C3926	Canon C3935	Canon C5850	Canon C5870	Canon C270
Technology	Laser	Laser	Laser	Laser	Laser	Laser
Monochrome copying, printing, scanning & faxing only	N/A	N/A	N/A	N/A	N/A	N/A
Color copying, color printing, color scanning & monochrome faxing	Yes	Yes	Yes	Yes	Yes	Yes
Rated speed	26	26	35	50	70	70+
Maximum copy/print size	12 5/8 x 18	12 5/8 x 18	12 5/8 x 18	12 5/8 x 18	12 5/8 x 18	13 x19
FCT (First-Copy Time)	5.9sec	5.9sec	4.9sec	3.5sec	3.5 sec	4.8sec
ADF (Automatic Document Feeder)	Yes	Yes	Yes	Yes	Yes	Yes

RADF (Reversing Automatic Document Feeder)	N/A	N/A	N/A	N/A	N/A	N/A
Duplexing (all units and drivers must default to duplex mode for both copying and printing)	Yes	Yes	Yes	Yes	Yes	Yes
Single-position Stapling Finisher	Yes	Yes	Yes	Yes	Yes	Yes
Sheet capacity of finisher	3250	3250	3250	3250	3250	3500
Separate finisher trays/locations for prints, faxes & copies	2 trays	2 trays	2 trays	2 trays	2 trays	3 trays
Fax Boards	Option	Option	Option	Option	Option	Option
Scan-to-email (with LDAP authentication)	Yes	Yes	Yes	Yes	Yes	Yes
Scan-to-XMedius Cloud Fax Server	Yes	Yes	Yes	Yes	Yes	Yes
Scan-to-shared folder (SharePoint)	Yes	Yes	Yes	Yes	Yes	Yes
Secure (passwordprotected) Printing	Yes	Yes	Yes	Yes	Yes	Yes
Console	N/A	N/A	N/A	N/A	Yes	Yes
Number of paper drawers (excluding bypass)	2	2	2	2	2	4

Total sheet capacity of drawers (excluding bypass)	1100	1100	1100	1100	1100	3550
Stack-feed bypass	Yes – 100	Yes – 100	Yes – 100	Yes – 100	Yes – 100	Yes – 250
Auto tray-switching	Yes	Yes	Yes	Yes	Yes	Yes
Guaranteed per-unit minimum monochrome volume						
Guaranteed per-unit minimum color volume						
Optional Features						