

EXHIBIT A-1.1

COPIER / MFD SPECIFICATIONS, MODELS TO BE INSTALLED

The CONTRACTOR shall install Copier/MFDs and related accessories and software with the following specified working functionality and guaranteed minimum volumes for each Segment as listed and described below.

A. COPIER/MFD GENERAL SPECIFICATIONS

Segment	1	2	3	4	5	6
Device Model Numbers	imageCLASS 1238 FFP	Canon 4925	Canon 4935	Canon 4945	Canon 6980	Canon 8995
Technology	Laser	Laser	Laser	Laser	Laser	Laser
Monochrome copying, printing, scanning & faxing only	Yes	Yes	Yes	Yes	Yes	Yes
Color copying, color printing, color scanning & monochrome faxing	N?A	N/A	N/A	N/A	N/A	N/A
Rated speed	40	25	35	45	80	95
Maximum copy/print size	8 ½ x 14	11 ¾ x 17	11 ¾ x 17	11 ¾ x 17	11 ¾ x 17	13 x 19
FCT (First-Copy Time)	5.3 sec	5.2sec	3.8sec	3.8sec	3.1sec	2.7sec
ADF (Automatic Document Feeder)	Yes	Yes	Yes	Yes	Yes	Yes

RADF (Reversing Automatic Document Feeder)	N/A	N/A	N/A	N/A	N/A	N/A
Duplexing (all units and drivers must default to duplex mode for both copying and printing)	Yes	Yes	Yes	Yes	Yes	Yes
Single-position Stapling Finisher	N/A	Yes	Yes	Yes	Yes	Yes
Sheet capacity of finisher	N/A	3250	3250	3250	3500	4250
Separate finisher trays/locations for prints, faxes & copies	1 tray	2 trays	2 trays	2 trays	3 trays	3 trays
Fax Boards	Inc	Option	Option	Option	Option	Option
Scan-to-email (with LDAP authentication)	Optional	Yes	Yes	Yes	Yes	Yes
Scan-to-XMedius Cloud Fax Server						
Scan-to-shared folder (SharePoint)	Yes	Yes	Yes	Yes	Yes	Yes
Secure (passwordprotected) Printing	Yes	Yes	Yes	Yes	Yes	Yes
Console	N/A	N/A	N/A	N/A	Yes	Yes
Number of paper drawers (excluding bypass)	2	2	2	2	4	4

Total sheet capacity of drawers (excluding bypass)	900	1100	1100	1100	4100	4100
Stack-feed bypass	Yes-100	Yes – 80	Yes – 80	Yes – 80	Yes – 100	Yes – 100
Auto tray-switching	N/A	Yes	Yes	Yes	Yes	Yes
Guaranteed per-unit minimum monochrome volume						
Guaranteed per-unit minimum color volume						
Optional Features						